



TENARIS.010A2

DELPHION[Select CR](#)**RESEARCH****PRODUCTS****INSIDE DELPHION**[Log Out](#)[Work Files](#)[Saved Searches](#)[My Account](#)[Search: Quick/Number](#)[Boolean](#)[Advanced](#)[Derwent](#)[Help](#)

The Delphion Integrated View

Get Now: ☒ PDF | [File History](#) | [Other choices](#)Tools: Add to Work File: [Create new Work File](#) View: INPADOC | Jump to: [Top](#) Go to: [Derwent](#)[Email this to a friend](#)**Title: JP63230851A2: LOW-ALLOY STEEL FOR OIL WELL PIPE EXCELLENT IN CORROSION RESISTANCE****Derwent Title:** Low alloy steel, used for oil wells - contg. carbon, silicon, manganese, sol aluminium nitrogen, aluminium-nitride, titanium zirconium and iron [[Derwent Record](#)]**Country:** JP Japan**Kind:** A DOC. LAID OPEN TO PUBL. INSPEC. [PUBLISHED FROM 1971 ON] ¹**Inventor:** OKADA YASUTAKA;
IKEDA AKIO;
KANEKO TERUO;**Assignee:** SUMITOMO METAL IND LTD
[News, Profiles, Stocks and More about this company](#)**Published / Filed:** 1988-09-27 / 1987-03-20**Application Number:** JP1987000067024**IPC Code:** Advanced: [C22C 38/00](#); [C22C 38/14](#); [C22C 38/38](#);
Core: more...
IPC-7: [C22C 38/00](#); [C22C 38/14](#); [C22C 38/38](#);**Priority Number:** 1987-03-20 JP1987000067024**Abstract:** PURPOSE: To develop a high-strength low-alloy steel for oil well excellent in corrosion resistance, particularly in resistance to sulfide stress corrosion cracking, by using, as a steel stock for oil well, a steel stock having a composition in which Ti and Zr for improving corrosion resistance are added and AlN content is minimal.CONSTITUTION: As a steel stock for oil well pipe and oil transport pipe used in the development of oil well and gas field, a low-alloy steel which has a composition containing, by weight, 0.15W0.45% C, 0.10W1.0% Si, 0.3W1.8% Mn, <0.010% sol. Al, N in an amount satisfying $N < [0.0020 + (Ti\% + Zr\%/8)]\%$, and <0.0050% AlN and further containing 0.005W0.10% Ti and/or 0.010W0.20% Zr or further containing one or more kinds among 0.05W2.00% Cr, 0.02W0.80% Mo, 0.005W0.20% Nb, 0.005W0.20% V, and 0.0001W0.0030% B is used. In this way, the low-alloy steel excellent in strength and corrosion resistance and having superior characteristics as a stock for oil well pipe, etc., can be obtained.

COPYRIGHT: (C)1988,JPO&Japio

INPADOC Legal Status: None **Get Now:** [Family Legal Status Report](#)**Family:** [Show 26 known family members](#)**Other Abstract Info:** [DERABS C88-312370](#) [DERC88-312370](#)[Nominate this for the Gallery...](#)[View Image](#)

1 page

Copyright © 1997-2009 Thomson Reuters

[Subscriptions](#) | [Web Seminars](#) | [Privacy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact Us](#) | [Help](#)